

Emiltrolley® MID



[IT] Carrello per trasporto ed erogazione di soluzioni a base di Urea **certificato MID**.

[EN] Special trolley for transport and delivery of DEF, **MID certified**.



Contalitri digitale ad alta precisione ad ingranaggi ovali certificato secondo la norma Mid MI-005 direttiva europea 214/32/UE.

Visualizza tutti i dati di ogni singola erogazione (quantità, data/ora, numero progressivo) e memorizza fino a 2000 operazioni, facilmente richiamabili per successivi controlli o verifiche.

High precision digital meter with oval gears **certified according to the Mid MI-005 standard, European directive 214/32/EU**.

It displays all the data of each single delivery (quantity, date / time, progressive number) and stores up to 2000 operations which can be easily recovered for analysis and check.



1. Chiave di accensione del sistema per evitare prelievi non autorizzati
System starting key to avoid unauthorized supplies
2. Pulsante di emergenza
Emergency button
3. Indicatore di carica della batteria
Battery charge indicator
4. Stampante termica: esegue la stampa dei singoli report completa di tutti i dati validi ai fini fiscali, al termine di ogni erogazione.
Thermal printer: prints individual reports complete with all data valid for tax purposes at the end of each supply



Portable delivery system on wheels for the supplying of AdBlue®/DEF contained in 60 or 200 litres drums, equipped with MID MI-005 certified meter for re-sale transactions.

EMILTROLLEY MID is complete with 12V stainless steel pump, an automatic air discharge device, stainless steel degasser, pump block pressure switch, 2 m pressostato di blocco pompa, tubo di mandata da un 1/2" da 2 m, pistola con arresto automatico, contalitri elettronico e stampante per l'emissione dello scontrino con i dati di erogazione.

The unit has been developed to be **autonomous** thanks to an internal 12V long-duration battery and complete with a 230V battery charger, thus allowing a constant use **regardless of electricity availability**.

OPTIONAL: riscaldatore elettrico
Coperta termica coprifusto e guaina termica del tubo di mandata per l'impiego in condizioni ambientali particolarmente rigide.

OPTIONAL: electric heater
Thermal cover for drums and thermal sheath of delivery hose for use in rigid and adverse environmental conditions.



CARATTERISTICHE TECNICHE E DIMENSIONALI:

- Maniglia superiore per la movimentazione.
- 4 ruote antiforatura di cui 2 fisse e 2 girevoli con freno.
- Valvola di sfalto superiore.
- Attacco rapido per aspirazione da fusti.
- Supporto porta pistola laterale.

Modello Model	Fusto Drum	Portata max Max load	Pressione max Max pressure	Alimentazione Power supply	Assorbimento Power consumption	Peso Weight	Dimensioni (LxPxH) Dimensions (WxPxH)
	l	U/min	bar	Volt	Ampere	kg	mm
6796MID	60	10	4	12	36	40	450x720x1050
6787MID	200	10	4	12	36	55	650x900x1150

TECHNICAL SPECIFICATIONS AND DIMENSIONS:

- Top handle for easy moving.
- 4 puncture proof castor wheels, 2 fixed and 2 swivel with brakes.
- Safety ball valve.
- Quick coupling for suction from drums.
- Side nozzle holder.